



- NOTES:
1. ALL SUCTION PIPING TO BE 1/2" SW, SCH 40, 316SS. UNLESS OTHERWISE NOTED.
 2. ALL DISCHARGE PIPING TO BE 1/2" OD, 316SS TUBING UNLESS OTHERWISE NOTED.
 3. PUMP OUTPUT: 1.14 LPH (0.30 GPH) RATED, 2.12 LPH (0.56 GPH) MAX.
 4. DISCHARGE OPERATING PRESSURE: 65 KGF/CM²G (924.5 PSIG).
 5. DISCHARGE MAX PRESSURE: 70 KGF/CM²G (995 PSIG).
 6. ELASTOMERS: VITON.
 7. DESIGNED FOR NALCO BT-2600.
 8. MOUNTED ON COMMON SKID WITH 82-PU-003 AND 82-PU-004.

SUPERIOR INDUSTRIAL EQUIPMENT
C13314-101

REV	DESCRIPTION	DATE	BY	CHK'D	APP'D
4	FINAL REVISION	07/08/14	SK	GM	KB
3	RELEASED FOR APPROVAL	03/27/14	PR	KB	KB
2	RELEASED FOR APPROVAL	02/08/14	PR	KB	KB
1	RELEASED FOR APPROVAL	12/21/13	PR	KB	KB

THIS DOCUMENT IS TECHNICAL PROPERTY AND CANNOT BE USED BY OTHERS FOR ANY PURPOSE, WITHOUT PRIOR WRITTEN CONSENT. Quality documents of property of customer is not part unless otherwise in clear made in form unless pneumatic submittance.

37430V080201182PU002942
 102-82-Z-102-002-002
 82-Z-102-002-002

Acceptance Status Code	Discipline	Signature	Signature	Date
A	Accepted			
C	Accepted with Comment, Resubmit			
R	Commented - Resubmit for Acceptance			
N	Not Accepted, Rejected			

TITLE - **82-PU-002 PHOSPHATE INJECTION SYSTEM P&ID DRAWING**
 PLANT - **Impulse** **OND. SCALE - Scale only** **GRAPHIC SCALE - Scale graph** **CLIENT REF. - RE. Clarke**
Armonio & Process OSBL **DO NOT SCALE**